







## 330H TWO MAN HOLE DIGGER

The time proven 300 Series Hole Diggers are designed to tackle a wide range of construction related hole digging projects...from simple backyard fencing to complex landscaping and soil sampling. Each built with oversized bearings, heat treated shafts and precision, machine cut gears that has created an industry wide reputation for delivering long service life and exceptional ROI. All with the power and performance to dig up to 18 inch diameter (457 mm) diameter holes in a wide variety of soil classifications. The unique Comfort-Flex™ operator handles actually flex under load to help absorb vibration and kickback forces encountered. This feature dramatically reduces operator fatigue, increases productivity rates and enhances jobsite safety. For use with the 4400 Series earth augers and 5500 Series auger extensions.

## **FEATURES**

- All metal centrifugal clutch
- Precision, spur gear transmission
- Comfort-Flex<sup>™</sup> operator handles
- Magura® twist grip throttle control

## **SPECIFICATIONS**

Starter Fuel Gasoline, unleaded, automotive grade Transmission Maximum Digging Torque Nominal Auger Rotation Speed Auger Drive Connection Available Auger Digging Length Available Auger Extensions Weight (less auger)  5.5 HP (4.1 kw) Honda GXV160, 4-stroke Hand rewind Gasoline, unleaded, automotive grade Totally enclosed, spur gear, oil lubricated 190 ft lbs (225 N.m) 144 RPM, no load 1-3/8 inch (35 mm) heaxgon 2 inch (51 mm) to 18 inch (457 mm) 36 inch (914 mm) 15 inch (381 mm), plain-tube type. 36 inch (914 mm), continuous flighted. 71 lbs (32 kg)		
Transmission  Maximum Digging Torque Nominal Auger Rotation Speed Available Auger Digging Length  Available Auger Extensions  Fuel Gasoline, unleaded, automotive grade Totally enclosed, spur gear, oil lubricated 190 ft lbs (225 N.m) 144 RPM, no load 1-3/8 inch (35 mm) heaxgon 2 inch (51 mm) to 18 inch (457 mm) 36 inch (914 mm) 15 inch (381 mm), plain-tube type. 36 inch (914 mm), continuous flighted.	Engine	5.5 HP (4.1 kw) Honda GXV160, 4-stroke
Transmission  Maximum Digging Torque  190 ft lbs (225 N.m)  Nominal Auger Rotation Speed  Auger Drive Connection  Available Auger Diameter Range  Standard Auger Digging Length  Available Auger Extensions  Totally enclosed, spur gear, oil lubricated  190 ft lbs (225 N.m)  144 RPM, no load  1-3/8 inch (35 mm) heaxgon  2 inch (51 mm) to 18 inch (457 mm)  36 inch (914 mm)  15 inch (381 mm), plain-tube type.  36 inch (914 mm), continuous flighted.	Starter	Hand rewind
Maximum Digging Torque  Nominal Auger Rotation Speed Auger Drive Connection  Available Auger Diameter Range  Standard Auger Digging Length  Available Auger Extensions  Oil lubricated  190 ft lbs (225 N.m)  144 RPM, no load  1-3/8 inch (35 mm) heaxgon  2 inch (51 mm) to 18 inch (457 mm)  36 inch (914 mm)  15 inch (381 mm), plain-tube type.  36 inch (914 mm), continuous flighted.	Fuel	Gasoline, unleaded, automotive grade
Nominal Auger Rotation Speed Auger Drive Connection  Available Auger Diameter Range Standard Auger Digging Length  Available Auger Extensions  144 RPM, no load 1-3/8 inch (35 mm) heaxgon 2 inch (51 mm) to 18 inch (457 mm) 36 inch (914 mm)  15 inch (381 mm), plain-tube type. 36 inch (914 mm), continuous flighted.	Transmission	, ,
Auger Drive Connection  1-3/8 inch (35 mm) heaxgon  2 inch (51 mm) to 18 inch (457 mm)  Standard Auger Digging Length  36 inch (914 mm)  Available Auger Extensions  1-3/8 inch (35 mm) heaxgon  2 inch (51 mm) to 18 inch (457 mm)  36 inch (914 mm), continuous flighted.	Maximum Digging Torque	190 ft lbs (225 N.m)
Available Auger Diameter Range 2 inch (51 mm) to 18 inch (457 mm) 36 inch (914 mm)  Available Auger Extensions 2 inch (51 mm) to 18 inch (457 mm) 36 inch (914 mm), plain-tube type. 36 inch (914 mm), continuous flighted.	Nominal Auger Rotation Speed	144 RPM, no load
Standard Auger Digging Length  36 inch (914 mm)  15 inch (381 mm), plain-tube type. 36 inch (914 mm), continuous flighted.	Auger Drive Connection	1-3/8 inch (35 mm) heaxgon
Available Auger Extensions  15 inch (381 mm), plain-tube type. 36 inch (914 mm), continuous flighted.	Available Auger Diameter Range	2 inch (51 mm) to 18 inch (457 mm)
36 inch (914 mm), continuous flighted.	Standard Auger Digging Length	36 inch (914 mm)
Weight (less auger) 71 lbs (32 kg)	Available Auger Extensions	, , , , , , , , , , , , , , , , , , , ,
	Weight (less auger)	71 lbs (32 kg)



All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF01111031